



4-Axis Dental Mill

DWX-4

Roland DWX-4. Dental Milling Machine.

Roland is leading the digital dental revolution.

Today, digital dental technologies are transforming every aspect of the dental industry. The days of tedious, manual production of crowns, copings and bridges are fast disappearing. The latest technological advancements in scanning, CAD/CAM software and

CNC milling allow digital dental labs to deliver custom production with speed and precision. Better fit and aesthetics promote patient satisfaction, while labs enjoy greater productivity with faster turnaround and optimal accuracy and repeatability.



Small footprint, big results.

The Roland DWX-4 is the most compact and user-friendly dental milling machine available. Like its larger family member the DWX-51D, it is capable of milling a wide variety of materials with reliable precision. Now, you can produce dental prosthetics with consistent accuracy at a very affordable price.



Built for any size lab.

With its small footprint and entry-level price, the DWX-4 is ideal for small and mid-size labs not yet using digital tools, or for those labs with scanners who no longer wish to outsource production. It's also perfect for larger labs needing a second device for urgent jobs that don't tie up their larger production mills. You can economically mill a single crown or small bridge quickly and easily.

A wide variety of materials.

The DWX-4 is equipped to mill standard blocks and pin-type materials, including wax, PMMA, Zirconia and composite resin.



Showing optional block adaptor ZV-4D.

Powerful yet easy to use.

The DWX-4 combines simultaneous 4-axis milling with simple one-button operation. An automated tool changer provides two tools for precision milling from start to unattended finish. Monitoring production is enhanced by the large viewing area and LED-lit interior. A status light alerts the operator of any errors or malfunction to help prevent wasted time and materials and enabling lab technicians to carry out the milling process with confidence.



Economical open architecture.

Open architecture allows the DWX-4 to work with the latest materials and CAD/CAM software so you're never limited by older technology. If you already have a production solution, the DWX-4 works seamlessly with your existing scanner and compatible CAD/CAM software while eliminating the need to rely on a single source for materials. Compatible with RML-1 and NC code, the DWX-4 interfaces with your computer through a USB 1.1 connector.



Virtual Machine Panel.

Unlike traditional CNC mills, Roland has replaced the complex controls with a user-friendly Virtual Machine Panel (VPanel) which operates machine diagnostics and the calibration and milling processes right from your computer desktop. The VPanel also tracks overall machine time for maintenance purposes.

The loniser is always active during milling process.



loniser off.



loniser on.

Clean cutting area for precision milling.

The DWX-4 is equipped with an integrated air blower that prevents excessive dust buildup and a negative ion generator that neutralises static electricity when milling PMMA. Adding to peace of mind, the DWX-4 can be connected to your chosen dust collection system and sensor that prevents the machine from starting if the vacuum is inadvertently left off.

Growth potential.

Highly scalable, the DWX-4 offers multicasst capability that allows you to connect up to four Roland machines to one computer, making it easier than ever for dental labs to expand their business and increase their production capacity. The DWX-4 dental milling machine lets labs control the entire process in-house with a single software seat, minimising your investment in time and money.

Backed by Roland.

Roland dental milling machines combine superior performance with legendary reliability. Tens of thousands of Roland users in more than 133 countries rely on Roland's unmatched customer service and support. As a company, Roland DG's ISO 9001:2008 and 14001 certifications assure consistent quality in manufacturing.

DWX-4 shown with optional 4 bay tool charger.



| Specifications | |
|---------------------------|---|
| Cuttable Material | Zirconia (pre-sintered), wax, PMMA and composite resin |
| Loadable workpiece shape | Block |
| | PIN type |
| Operating speed | XYZ axis: 6 to 1800 mm/min. |
| Spindle motor | Brushless DC motor |
| Spindle speed | 6,000 to 30,000 rpm |
| Rotary axis travel angle | A: $\pm 360^\circ$ |
| Number of tools housed | 2 (4 tool adapter ZAT-4D sold separately) |
| Attachable tool | Shank diameter: 4 mm, Length: 40 to 55 mm |
| Compatible compressed air | 0.02 to 0.2 MPa |
| Interface | USB (compliant with Universal Serial Bus Specification Revision 1.1) |
| Control command set | RML-1, NC code |
| Power requirements | AC100 to 240 V $\pm 10\%$, 50/60 Hz, 0.8 to 0.4 A (overvoltage category II, IEC 60664-1) |
| Power consumption | Approx. 70 W |
| Operating noise | During operation: 70 dB (A) or less (when not cutting) During standby: 40 dB (A) or less |
| External dimensions | Width x Depth x Height: 340x365x405 mm |
| Weight | 22 kg |
| Installation Environment | Indoor Use, altitude: up to 2000 m Temperature: 5 to 40 °C Relative humidity: 35 to 80 % (no condensation) Ambient pollution degree: 2 (as specified by IEC 60664-1) Short-Term Temporary Overvoltage: 1440 V Long-Term Temporary Overvoltage: 490 V |
| Included items | Power cord, USB cable, Manual, Software Package CD-ROM, Detection pin, Automatic correction jig, Clamp for block workpiece, Hexagonal screwdriver, spanner, Tool holder, Tool positioner, Dust collection hose, Regulator. |

| System Requirements for USB Connection | |
|---|--|
| Computer | Model preinstalled with the 32- or 64-bit edition of Windows XP, Vista, 7, 8, 10 or upgraded computer originally preinstalled with Windows XP or later |
| USB cable | Use the included USB cable |

| Options | | |
|----------------------|--------------|---|
| Item | Model | Description |
| 4-Position ATC *1 *2 | ZAT-4D | Number of tools housed: 4 Loadable workpiece shape: PIN type (small) |
| Multi-Pin Clamp *2 | ZV-4D | Loadable workpiece supported: PIN type (small) Number of loadable workpieces: max. 4 Loadable workpiece sizes: For 4 workpieces (Width x Depth x Height): Max. 14,5 x 21 x 20 mm For 3 workpieces (Width x Depth x Height): Max. 20 x 21 x 20 mm |
| Spindle Unit | ZS-4D | For replacement |
| Milling Bur | ZDB-100D | R1,0 mm billing bur for composite resin (2 mm diameter) |
| | ZDB-50D | R0,5 mm billing bur for composite resin (1 mm diameter) |
| | ZDB-30D | R0,3 mm billing bur for composite resin (0.6 mm diameter) |

*1 The 4-position ATC works with Roland's Virtual Machine Panel (Vpanel) ver. 1.1 or later

*2 The multi-pin clamp cannot be used simultaneously with the 4-position ATC

Roland reserves the right to make changes in specifications, materials or accessories without notice. Your actual output may vary. For optimum output quality, periodic maintenance to critical components may be required. Please contact your Roland dealer for details. No guarantee or warranty is implied other than expressly stated. Roland shall not be liable for any incidental or consequential damages, whether foreseeable or not, caused by defects in such products. Three-dimensional shapes may be protected under copyright. All trademarks are the property of their respective owners. Roland DG Corp. has licensed the MMP technology from the TPL Group.



Αθήνα: Μαρίνου Αντύπα 14, Αλιμος **Τηλ.:** 210-98.45.771 **Fax:** 210-98.45.081
Θεσσαλονίκη: Λεωφόρος 28ης Οκτωβρίου 142 **Τηλ.:** 2310-67.29.42 **Fax:** 2310-62.66.10

web: <http://www.rolanddg.gr/>, <http://www.atlasdigital.gr/>

email: info@atlasdigital.gr

